

MATERIAL SAFETY DATA SHEET (Page 1 of 3)

This form is regarded to be in compliance with 29 CFR Part 1910.1200

SECTION 1 : IDENTIFICATION

PRODUCT NAME: EzNails, Inc EZHAND SANITIZER (62% ALCOHOL/VOL)

Manufacturer's Name: EzNails, Inc Proprietary Blend
Address : 10385 Los Alamitos Blvd. CAS #
City, State, Zip : Los Alamitos, CA. 90720
Business Telephone : (562)598-3966
Emergency Telephone : (800)535-5053

SECTION 2: PHYSICAL DATA

Specific Gravity 25/25 : .852 @ 60/60F Boiling Point : Deg C. 201 F
Vapor Pressure : 38mm Hg @ 20 C Physical State : Liquid
Vapor Density [Air =1] : 1.26 Evaporation Rate: 1.5
Autoignition Temp: 951 F Odor : Odorless
Solubility in Water : SOLUBLE IN WATER

SECTION 3 : FIRE AND EXPLOSION HAZARD DATA

Flash Point (Closed Cup F) : Deg 268 F

Extinguishing Media : []Water [X]CO₂ []Dry Chemical [X]Foam []Water Fog

Special Fire Fighting Procedures : Protect from heat and flame

Unusual Fire and Explosion Hazards : Dense Smoke May be Generated, Carbon Monoxide, Carbon Dioxide, and other oxides may be generated.

NFPA FLAMMABILITY CODE : 1

SECTION 4 : REACTIVITY DATA

Stability : Presents no significant reactivity hazard, not pyrophoric nor reactive with water.

Incompatibility (Materials to avoid): AVOID CONTACT WITH OXIDIZERS

Hazardous Combustion or Decomposition Products:

Burning liberates CO, CO₂ and smoke. Does not form explosive mixtures with organic materials. Does not undergo explosive decomposition and is shock stable. It is not an oxygen donor

Hazardous Polymerization :

Will NOT undergo spontaneous exothermic polymerization.

NFPA REACTIVITY CODE : 0

MATERIAL SAFETY DATA SHEET (Page 2 of 3)

PRODUCT NAME: EzNails, Inc HAND SANITIZER (62% ALCOHOL/VOL)

SECTION 5 : SPILL OR LEAKAGE PROCEDURES

Cleanup of spills or accidental release of material:
Soak up with suitable absorbent.

Waste Disposal Methods :

Incineration or sanitary landfill in accordance with local, state and federal regulations and consistent with good ecological practices.

SECTION 6 : SPECIAL PROTECTION INFORMATION

Respiratory : Use NIOSH/MSHA Approved Respirator if TLV is exceeded

Ventilation : General Mechanical

Protective Gloves : Volatile Resistant if skin contact is anticipated

Eye Protection : Splash proof goggles if handling methods warrant them.

Other Protective Equipment :

SECTION 7 : EMERGENCY AND FIRST AID PROCEDURES

Eye (contact) : In the event of accidental contact with eyes, irrigate copious amounts of water; if irritation persists obtain medical advice.

Skin (contact): Remove contaminated clothing. Flush exposed areas with copious amounts mild soap and water. Material may remove some of the natural oils in the skin. If irritation persists obtain medical advice.

Inhalation : Move to fresh air. Give artificial respiration if breathing has stopped.

Ingestion : Give either 10 grains of potassium permanganate or one tablespoon of medical charcoal in a tumbler full of water. Emetics or stomach tube should be used by a physician. Give gastric lavage followed by saline catharsis

