

Material Safety Data Sheet ACRYLIC TOPCOAT UV Page 1 of 5

Revised Date: 5/01/05 | Replaces Date: 12/16/04

MSDS#: KIT121304-UVT

Product Name: ACRYLIC TOPCOAT UV MSDS Initial

Approval Date:

12/16/2004

Chemical Name: Nail Laquer MSDS Prepared by:

BSQ

Family: TOP COAT **Manufacturer:** KEYSTONE INDUSTRIES

616 Hollywood Ave. Cherry Hill, NJ 08002

Product Use: NAIL TOP COAT **Emergency Phone Numbers:** (800) 535 - 5053

Product #: 4020094 **Information Contacts:** (856)-663-4700

Chemical Identity CAS

Numbers

EINECS# INCI Name Exposure Limits Carcinogen %

OSHA ACGIH

TWA/STEL TWA/STEL IARC/NTP/OSHA

Toluene 108-88-3 203-625-9 Toluene 200ppm 50ppm 3/No/No 35-45

Acrylates Copolymer 25035-69-2 N/E Acrylates Copolymer N/E N/E Not Listed 40-50

n-Butyl Acetate 123-86-4 204-658-1 Butyl Acetate 150 ppm 150 ppm Not Listed 10-20

2,5-thiophenediylbis(5-tertbutyl-

1,3-benzoxazole)

7128-64-5 230-426-4 Bis(T-butyl benzoxazolyl)

Thiophene

N/E N/E Not Listed 0-1

D&C Violet #2 81-48-1 201-353-5 Violet 2/CI60725 N/E N/E Not Listed 0-1

N/E - None Established

N/R - Not Reviewed

N/DA - No Data Available

N/A - Not Applicable

Hazard Symbols: Xi, F **Risk Phrases:** R11, R20/22, R36/37/38 **Safety Phrases:** S7/9, S16, S24/25, S33, S37/39, S45

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

• Flammable liquid and vapor!

- May cause allergic skin reaction.
- May cause eye irritation.
- May cause respiratory tract irritation.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry Inhalation, skin contact, eye contact

Eye Exposure causes eye irritation. Symptoms include stinging, tearing, redness and swelling.

Skin Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking, and skin burns.

Ingestion Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing

large amounts may be harmful. This material can get into the lungs during swallowing or vomiting.

Inhalation Vapor and mist are irritating to mucous membrane. Breathing small amounts during normal handling

is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually

EzNAILS, Inc.

11652 Monarch Street
Garden Grove CA 92841
562-598-3966 Fax 598-8096.

occur at air concentrations higher than the recommended exposure limits.

Sub-Chronic Effects It may cause headaches,nausea,vomiting and narcotic effect if over-exposed.

NOTE: Refer to Section 11, Toxicological Information for Details

First Aid for Eye If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while

holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

First Aid for Skin Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention.

First Aid for Inhalation Remove to fresh air.If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention.

Material Safety Data Sheet ACRYLIC TOPCOAT UV Page 2 of 5

Revised Date: 5/01/05 | Replaces Date: 12/16/04

MSDS#: KIT121304-UVT

First Aid for Ingestion If individual is drowsy or unconscious. do not give anything by mouth; place individual on the leftside with the head down.Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Flash Point Flammable Limit Auto-ignition Temperature

(°F/°C) (vol%) (vol%)

TAG Closed: 68°F/20°C 400 ppm

Method:

Extinguishing Media: Foam, dry chemical, cold water spray.

Fire Fighting

Instructions:

Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a safe distance and protected location.

Unusual Hazards: Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may produce

toxic products CO, Carbon dioxide and oxides of nitrogen. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.

Spill or Release

Procedures

Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

Handling Keep containers cool and dry. Keep away from heat, light and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash thoroughly after handling.

Storage Store in well ventilated area. Store @ 70°F+/- 15°F (21°C+/-8°C), allow some air space above liquid

EzNAILS, Inc.

11652 Monarch Street
Garden Grove CA 92841
562-598-3966 Fax 598-8096.

level. Keep containers closed while not in use.

Explosion Hazard Vapors are heavier than air and may travel along the ground or may be move by ventilation and

ignited by pilot lights, other flames, sparks, heaters, smoking or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Engineering Controls Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use

process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Personal Protective Equipment

General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product . Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Skin Protection Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Respiratory Protection A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible

under certain limited circumstances where airborne concentrations are expected to exceed exposure limits.

Material Safety Data Sheet ACRYLIC TOPCOAT UV Page 3 of 5

Revised Date: 5/01/05 | Replaces Date: 12/16/04

MSDS#: KIT121304-UVT

Protection provided by nuisance level organic vapor dust masks can be used, however the use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Appearance Odor & Odor Threshold pH Specific Gravity Viscosity % Volatile

Blue to Violet, viscous liquid fruity ester like odor N/A (H₂O=1): 0.98 N/DA W/W %: 99+

Boiling Point/

Decomposition

Octanol/Water

Vapor

Vapor

Evaporation

Ignition

Solubility

Freezing Point

Temperature Partitioning Coefficient

Log Po/w

Pressure Density Rate In Water

(20°C)

170°F(77°C) N/DA N/DA N/A (Air=1): 1 N/A N/A Insoluble

Flash Point Flammable Limit Auto-ignition Temperature

(°F/°C) (vol%) (vol%)

TAG Closed: 68°F/20°C 400 ppm

Stability: Incompatibility (Materials to Avoid):

Stable Avoid oxidizing agents, acids & bases (heat)

Hazardous Decomposition Products: Hazardous Polymerization:

Heated material produce NO₂ , CO₂ , CO Will not occur

Conditions to Avoid:

Heat, flame, ignition sources.

EzNAILS, Inc.

11652 Monarch Street
Garden Grove CA 92841
562-598-3966 Fax 598-8096.

Acute Oral Toxicity Acute Dermal Toxicity Acute Inhalation Toxicity Irritation - skin Irritation - Eye

No information available No information available No information available No information available No information available

Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

Sensitization Mutagenicity Sub-chronic Toxicity

No information available No information available No information available

Ecotoxicological Information

Acute Toxicity

To Fish

Acute Toxicity

to Invertebrates

Acute Toxicity

to Algae

Bioconcentration Toxicity to Sewage Bacteria

No information available No information available No information available

No information available

available

No information available

Chemical Fate Information

Biodegradability No information available

Chemical Oxygen Demand No information available

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility.

Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ

from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For

EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that

national or regional provisions may be in force.

DOT (49 CFR 172)

Material Safety Data Sheet ACRYLIC TOPCOAT UV Page 4 of 5

Revised Date: 5/01/05 | Replaces Date: 12/16/04

MSDS#: KIT121304-UVT

Proper Shipping Name: Flammable liquids, n.o.s., (toluene, butyl acetate), 3, UN1993, PGII

Identification Number: UN1993

Marine Pollutant: No

Special Provisions: T8, T31

Emergency Response Guidebook (ERG) #: 128

IATA (DGR):

Proper Shipping Name: Flammable liquids, n.o.s., (toluene, butyl acetate), 3, UN1993, PGII

Class or Division: 3

UN or ID Number: UN1993

Packaging Instructions:

Emergency Response Guidance (ICAO)#:

EzNAILS, Inc.

11652 Monarch Street
Garden Grove CA 92841
562-598-3966 Fax 598-8096.

IMO (IMDG):

Proper Shipping Name: Flammable liquids, n.o.s., (toluene, butyl acetate), 3, UN1993, PGII

Class or Division: 3.2

UN or ID Number: UN1993

Special Provisions & Stowage/Segregation: None

Emergency Schedule (EmS)#:

Other Information: Flash point = 20°C

US Federal Regulations

Clean Air Act: HAP/ODS This product contains the following hazardous air pollutants (HAPs):

- Toluene, CAS# 108-88-3

There are no ODS's (ozone depleting substances) as defined by the U. S. Clean Air Act.

Clean Water Act: Priority Pollutant This product contains the following Hazardous Substances as defined by the CWA:

- Toluene, CAS# 108-88-3
- Butyl Acetate, CAS# 123-86-4

Toluene can be found on the Priority Pollutant list. Toluene can be found on the Toxic Pollutant list per the CWA.

FDA: Food Packaging Status This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.

Occupational Safety and Health Act This product is considered to be hazardous under the OSHA Hazard Communication

Standard. Its hazard are:

- Immediate (acute) health hazard
- Fire hazard

RCRA This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261):

- Toluene CAS# 108-88-3, RCRA Code U220
- May contain Characteristic of Ignitability: RCRA Code: D001

SARA Title III: Section 302 (TPQ) This product contains no chemicals regulated under Section 302 as extremely hazardous substances.

SARA Title III: Section 302 (RQ) This product contains chemicals regulated under Section 302-304 as extremely

hazardous chemicals for emergency release notification ("CERCLA" List):

- Toluene CAS#: 108-88-3, RQ(Lbs)1000
- Butyl Acetate CAS#: 123-86-4, RQ(Lbs)5000

SARA Title III: Section 311-312: This product is considered to be hazardous under the OSHA Hazard Communication

Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are:

- Immediate (acute) health hazard
- Fire hazard

SARA Title III: Section 313: This product contains the following chemicals which are subject to the reporting requirements of

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

- Toluene CAS#: 108-88-3

TSCA Section 8(b): Inventory: This product contains chemicals listed on the TSCA inventory or otherwise complies

Material Safety Data Sheet ACRYLIC TOPCOAT UV Page 5 of 5

Revised Date: 5/01/05 | Replaces Date: 12/16/04

MSDS#: KIT121304-UVT

TSCA Significant New Use Rule:

with TSCA premanufacture notification requirements.

EzNAILS, Inc.

11652 Monarch Street
Garden Grove CA 92841
562-598-3966 Fax 598-8096.

None of the chemicals in this material have a SNUR under TSCA.

State Regulations

CA Right-to-Know Law:

California No Significant Risk Level:

Toluene, CAS#108-88-3, Butyl Acetate CAS #123-86-4

NONE

MA Right-to-Know Law: Toluene, CAS#108-88-3, Butyl Acetate CAS #123-86-4

NJ Right-to-Know Law: Toluene, CAS#108-88-3, Butyl Acetate CAS #123-86-4

PA Right-to-Know Law: Toluene, CAS#108-88-3, Butyl Acetate CAS #123-86-4

FL Right-to-Know Law: Toluene, CAS#108-88-3, Butyl Acetate CAS #123-86-4

MN Right-to-Know Law: Toluene, CAS#108-88-3, Butyl Acetate CAS #123-86-4

International Regulations

CDSL: Canadian Inventory

(on Canadian Transitional List)

Toluene CAS# 108-88-3 is on the DSL list. WHMIS = B2, D2B

Butyl Acetate CAS #123-86-4 is on the DSL list. WHMIS = B2, D1B, D2B

Acrylates Copolymer CAS # 25035-69-2 is on the DSL list. WHMIS = n/da

2,5-thiophenediylbis(5-tert-butyl-1,3-benzoxazole) CAS# 7128-64-5 is on the DSL List. WHMIS= n/da

D&C Violet #2 CAS# 81-48-1 is not considered to be a controlled product under WHMIS.

EINECS: European Inventory: **Acrylic TopCoat UV:**

- **HAZARD SYMBOLS: Xn, F: Harmful, Highly Flammable**
- **RISK PHRASES: R11, highly flammable, R20/22: Harmful by inhalation and if swallowed, R36/37/38: Irritating to eyes, respiratory system and skin**
- **SAFETY PHRASES: S7/9: keep container tightly closed and in a well ventilated place, S16: keep away from sources of ignition- no smoking, S24/25: avoid contact with skin and eyes, S33: take precautionary measures against static discharges, S37/39: wear suitable gloves and eye/face protection, S45: In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible)**

Hazard Rating System (Pictograms)

NFPA: HMIS:

2 3 1

Product Number – 4020094

Revised Sections since Last Version: 5/01/05 - #2, added ingred. % range.

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.

3

1 2

Flammability

Reactivity Health